



QMFZ2 Component - Plastics

Tuesday, April 14, 2009

E146413

KOTEC CORP

3-21-15 CHAYAMADAI MINAMI SAKAI OSAKA 590-0115 JP

Material Designation: **1340(#)**

Product Description: Polyphenylene Sulfide (PPS),.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
NC, BK	0.75	V-0	-	-	130	130	130	-	-
	3.0	V-0	-	-	130	130	130	-	-

CTI: - **IEC CTI (V):** - **HVTR:** - **D495:** - **IEC Ball Pressure (°C):** -

Dielectric Strength (kV/mm): - **Volume Resistivity (10^xohm-cm):** - **Dimensional Stability(%):** -
ISO Tensile Strength (MPa): - **ISO Flexural Strength (MPa):** - **ISO Heat Deflection (°C):** -
ISO Tensile Impact (kJ/m²): - **ISO Izod Impact (kJ/m²):** - **ISO Charpy Impact (kJ/m²):** -

Suffix optional excluding the letters "FR" and "FRT"

Report Date: 8/7/2008

Underwriters Laboratories Inc®

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.