



KOTEC CORP

21-15 3-CHO CHAYAMADAI SAKAI-SHI OSAKA 590-0115 JP

Material Designation: **K-30FR, K-30FRT#**

Product Description: Polycarbonate (PC), designated "Carbotex, Kotex" furnished as pellets.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
ALL	2.0	V-2	-	-	80	80	80	-	-
	3.0	V-0	1	2	80	80	80	-	-

CTI: - **IEC CTI (V):** - **HVTR:** - **D495:** - **IEC Ball Pressure (°C):** -

Dielectric Strength (kV/mm): -	Volume Resistivity (10^xohm-cm): -	Dimensional Stability(%): -
ISO Tensile Strength (MPa): -	ISO Flexural Strength (MPa): -	ISO Heat Deflection (°C): -
ISO Tensile Impact (kJ/m²): -	ISO Izod Impact (kJ/m²): -	ISO Charpy Impact (kJ/m²): -

Suffix optional excluding the letters "FR" and "FRT"

Report Date: 7/28/1992

Underwriters Laboratories Inc®

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.